

## Series 3D - Software Development System

Standard Vehicle Mount Display with breakout board for easy connection. Includes Software Developer's Guide and Developer Kit.

### 3D65 - 6.5-inch Display

- 416 MHz PXA270 processor
- 64MB SDRAM
- 64MB NAND program and file sys FLASH

**3D65DEV-1** Software Development System with 6.5-inch Display, Windows CE\*

**3D65DEV-1T** Software Development System with 6.5-inch touchscreen, Windows CE\*

Breakout board includes connectors for:

- 1 USB host port
- 3 CAN-bus port
- 3 NTSC/PAL video inputs
- 3 serial ports
- 10/100 ethernet port
- Input voltage: 9VDC to 32VDC



### 3D104 - 10.4-inch Display

- 416 MHz PXA270 processor
- 64MB SDRAM
- 64MB NAND program and file sys FLASH

**3D104DEV-1** Software Development System with 10.4-inch Display, Windows CE\*

**3D104DEV-1T** Software Development System with 10.4-inch touchscreen, Windows CE\*

Breakout board includes connectors for:

- 1 USB host port
- 3 CAN-bus port
- 3 NTSC/PAL video inputs
- 2 serial ports
- 3 inputs
- 2 outputs (200 mA max)
- 10/100 ethernet port
- Input voltage: 9VDC to 32VDC